




A-1 HARDWARE QUANTITY TABLE

SIGN LENGTH	SIGN DEPTH	UNITS REQUIRED
	See Note 6	See Note 5
15'-0" or less	4'-2" - 5'-0"	4
16'-0" - 24'-0"	4'-2" - 5'-0"	6
15'-0" or less	5'-10" - 10'-0"	8
16'-0" - 24'-0"	5'-10" - 10'-0"	12


STAINLESS STEEL BOLT




ű

9

TOP VIEW





FRONT VIEW

NOTES:

- 1. Refer to applicable Standard Plan for additional mounting details.
- 2. Mounting clamp shall be aluminum casting as specified in the Special Provisions.
- 3. Rectangular head bolt, hexagon stop nut, and flat washer shall be $\frac{1}{8}$ " diameter (18-8) stainless steel.
- 4. One unit of A-1 hardware shall consist of two sets of these components: clamp, bolt, nut and washer.
- Signs 9'-2" and 10'-0" in depth may be fabricated in three panel sections to avoid legend from being placed on a horizontal seam. Increase number of units of mounting hardware accordingly.

STATE OF CALIFORNIA DEPARTMENT OF TRANSPORTATION

TYPE A-1 MOUNTING HARDWARE **OVERHEAD LAMINATED** TYPE A PANEL TRUSS AND LIGHTWEIGHT SIGN STRUCTURES

NO SCALE

S87